

Welcome to iValve, a professional manufacturer for water control system

 English

Product Categories

[Gate Valve \(/portal/list/index/id/16.html\)](/portal/list/index/id/16.html)

[Non-Return Valve \(/portal/list/index/id/17.html\)](/portal/list/index/id/17.html)

[Hydraulic Control Valve \(/portal/list/index/id/18.html\)](/portal/list/index/id/18.html)

[Air Release/Vacuum Valve \(/portal/list/index/id/19.html\)](/portal/list/index/id/19.html)

[Butterfly Valve \(/portal/list/index/id/20.html\)](/portal/list/index/id/20.html)

[Strainer/Filter \(/portal/list/index/id/21.html\)](/portal/list/index/id/21.html)

[Foot Valve \(/portal/list/index/id/22.html\)](/portal/list/index/id/22.html)

[Fire Hydrant \(/portal/list/index/id/32.html\)](/portal/list/index/id/32.html)

[Globe Valve, Ball Valve \(/portal/list/index/id/36.html\)](/portal/list/index/id/36.html)

[DI Pipe Fittings \(/portal/list/index/id/37.html\)](/portal/list/index/id/37.html)

Foot Valve

Description

The foot valve is a kind of check valve. It is a valve used to prevent the medium in the pipeline from flowing back. The foot valve is opened when the medium flows downstream, and the foot valve is automatically closed when the medium flows backward. The foot valve is equipped with multiple water inlets on the bonnet, and is equipped with a screen to reduce the inflow of debris, which are not easy to be blocked.

Standards



Foot Valve

- Size range: DN50 - DN300
- Connection Ends: EN 1092-2, PN10/16
- Nominal Pressure: PN10/16
- Temperature Range: 0°C - 80°C
- Coating: Fusion bonded epoxy powder coating with min 250 microns thickness inside and outside



With over 15 years rich experience in the valves designing, manufacturing, marketing and exporting.

LOCATION

ADD: Jinqiao Road 97,YiAn ETDZ,
Tongling City, Anhui Province, P.R.CHINA.

CONTACT

Tel: 0086 0562-5855899

Fax: 0086 0562 6820566

Email: sales@ivalveflow.com (mailto:sales@ivalveflow.com)

Copyright © IVALVE TECH. (TONGLING) CO.,LTD. All rights reserved.